

NAME

gnutls_srp_set_server_credentials_file - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
int gnutls_srp_set_server_credentials_file(gnutls_srp_server_credentials_t res, const char *  
password_file, const char * password_conf_file);
```

ARGUMENTS

gnutls_srp_server_credentials_t res
is a **gnutls_srp_server_credentials_t** type.

const char * password_file
is the SRP password file (tpasswd)

const char * password_conf_file
is the SRP password conf file (tpasswd.conf)

DESCRIPTION

This function sets the password files, in a **gnutls_srp_server_credentials_t** type. Those password files hold usernames and verifiers and will be used for SRP authentication.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, or an error code.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>