

NAME

gnutls_tdb_set_store_commitment_func - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_tdb_set_store_commitment_func(gnutls_tdb_t tdb, gnutls_tdb_store_commitment_func  
cstore);
```

ARGUMENTS

gnutls_tdb_t tdb

The trust storage

gnutls_tdb_store_commitment_func cstore

The commitment storage function

DESCRIPTION

This function will associate a commitment (hash) storage function with the trust storage structure. The function is of the following form.

```
int gnutls_tdb_store_commitment_func(const char* db_name, const char* host, const char* service,  
time_t expiration, gnutls_digest_algorithm_t, const gnutls_datum_t* hash);
```

The *db_name* should be used to pass any private data to this function.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>