

NAME

gnutls_tdb_set_verify_func - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_tdb_set_verify_func(gnutls_tdb_t tdb, gnutls_tdb_verify_func verify);
```

ARGUMENTS

gnutls_tdb_t tdb

The trust storage

gnutls_tdb_verify_func verify

The verification function

DESCRIPTION

This function will associate a retrieval function with the trust storage structure. The function is of the following form.

```
int gnutls_tdb_verify_func(const char* db_name, const char* host, const char* service, const gnutls_datum_t* pubkey);
```

The verify function should return zero on a match, **GNUTLS_E_CERTIFICATE_KEY_MISMATCH** if there is a mismatch and any other negative error code otherwise.

The *db_name* should be used to pass any private data to this function.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>