

**NAME**

gnutls\_transport\_is\_ktls\_enabled - API function

**SYNOPSIS**

```
#include <gnutls/gnutls.h>
```

```
gnutls_transport_ktls_enable_flags_t gnutls_transport_is_ktls_enabled(gnutls_session_t session);
```

**ARGUMENTS**

gnutls\_session\_t session

is a **gnutls\_session\_t** type.

**DESCRIPTION**

Checks if KTLS is now enabled and was properly initialized.

**RETURNS**

**GNUTLS\_KTLS\_RECV**, **GNUTLS\_KTLS\_SEND**, **GNUTLS\_KTLS\_DUPLEX**, otherwise 0

**SINCE**

3.7.3

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>