

NAME

gnutls_transport_set_ptr2 - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_transport_set_ptr2(gnutls_session_t session, gnutls_transport_ptr_t recv_ptr,  
gnutls_transport_ptr_t send_ptr);
```

ARGUMENTS

gnutls_session_t session
is a **gnutls_session_t** type.

gnutls_transport_ptr_t recv_ptr
is the value for the pull function

gnutls_transport_ptr_t send_ptr
is the value for the push function

DESCRIPTION

Used to set the first argument of the transport function (for push and pull callbacks). In Berkeley style sockets this function will set the connection descriptor. With this function you can use two different pointers for receiving and sending.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>