

gnutls_transport_set_vec_push_function(3) gnutls gnutls_transport_set_vec_push_function(3)

NAME

gnutls_transport_set_vec_push_function - API function

SYNOPSIS

```
#include <gnutls/gnutls.h>
```

```
void gnutls_transport_set_vec_push_function(gnutls_session_t session, gnutls_vec_push_func  
vec_func);
```

ARGUMENTS

gnutls_session_t session
is a **gnutls_session_t** type.

gnutls_vec_push_func vec_func
a callback function similar to **writenv()**

DESCRIPTION

Using this function you can override the default writenv(2) function for gnutls to send data. Setting this callback instead of **gnutls_transport_set_push_function()** is recommended since it introduces less overhead in the TLS handshake process.

vec_func is of the form, ssize_t (*gnutls_vec_push_func) (gnutls_transport_ptr_t, const giovec_t * iov, int iovcnt);

SINCE

2.12.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_transport_set_vec_push_function(3)

gnutls

gnutls_transport_set_vec_push_function(3)

<https://www.gnutls.org/manual/>