

NAME

gnutls_x509_crl_dist_points_set - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_crl_dist_points_set(gnutls_x509_crl_dist_points_t cdp,  
gnutls_x509_subject_alt_name_t type, const gnutls_datum_t * san, unsigned int reasons);
```

ARGUMENTS

gnutls_x509_crl_dist_points_t *cdp*

The CRL distribution points

gnutls_x509_subject_alt_name_t *type*

The type of the name (of **gnutls_subject_alt_names_t**)

const gnutls_datum_t * *san*

The point name data

unsigned int *reasons*

Revocation reasons. An ORed sequence of flags from **gnutls_x509_crl_reason_flags_t**.

DESCRIPTION

This function will store the specified CRL distribution point value the *cdp* type.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0), otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>