

## NAME

gnutls\_x509\_crl\_get\_extension\_data - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_get_extension_data(gnutls_x509_crl_t crl, unsigned indx, void * data, size_t *  
sizeof_data);
```

## ARGUMENTS

gnutls\_x509\_crl\_t *crl*

should contain a **gnutls\_x509\_crl\_t** type

unsigned *indx* Specifies which extension OID to send. Use (0) to get the first one.

void \* *data* a pointer to a structure to hold the data (may be null)

size\_t \* sizeof\_*data*

initially holds the size of *oid*

## DESCRIPTION

This function will return the requested extension data in the CRL. The extension data will be stored as a string in the provided buffer.

Use **gnutls\_x509\_crl\_get\_extension\_info()** to extract the OID and critical flag. Use **gnutls\_x509\_crl\_get\_extension\_info()** instead, if you want to get data indexed by the extension OID rather than sequence.

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error code in case of an error. If you have reached the last extension available

**GNUTLS\_E\_REQUESTED\_DATA\_NOT\_AVAILABLE** will be returned.

## SINCE

2.8.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>