

NAME

gnutls_x509_crl_get_extension_info - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_get_extension_info(gnutls_x509_crl_t crl, unsigned indx, void * oid, size_t *  
sizeof_oid, unsigned int * critical);
```

ARGUMENTS

gnutls_x509_crl_t *crl*

should contain a **gnutls_x509_crl_t** type

unsigned *indx* Specifies which extension OID to send, use (0) to get the first one.

void * *oid* a pointer to store the OID

size_t * *sizeof_oid*

initially holds the maximum size of *oid* , on return holds actual size of *oid* .

unsigned int * *critical*

output variable with critical flag, may be NULL.

DESCRIPTION

This function will return the requested extension OID in the CRL, and the critical flag for it. The extension OID will be stored as a string in the provided buffer. Use **gnutls_x509_crl_get_extension_data()** to extract the data.

If the buffer provided is not long enough to hold the output, then * *sizeof_oid* is updated and **GNUTLS_E_SHORT_MEMORY_BUFFER** will be returned.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error code in case of an error. If you have reached the last extension available

GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE will be returned.

SINCE

2.8.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>