

**NAME**

gnutls\_x509\_crl\_get\_number - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_get_number(gnutls_x509_crl_t crl, void * ret, size_t * ret_size, unsigned int * critical);
```

**ARGUMENTS**

gnutls\_x509\_crl\_t *crl*

should contain a **gnutls\_x509\_crl\_t** type

void \* *ret*      The place where the number will be copied

size\_t \* *ret\_size*

Holds the size of the result field.

unsigned int \* *critical*

will be non-zero if the extension is marked as critical (may be null)

**DESCRIPTION**

This function will return the CRL number extension. This is obtained by the CRL Number extension field (2.5.29.20).

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error code in case of an error.

**SINCE**

2.8.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>