

NAME

gnutls_x509_crl_import - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_import(gnutls_x509_crl_t crl, const gnutls_datum_t * data, gnutls_x509_crt_fmt_t  
format);
```

ARGUMENTS

gnutls_x509_crl_t *crl*
The data to store the parsed CRL.

const gnutls_datum_t * *data*
The DER or PEM encoded CRL.

gnutls_x509_crt_fmt_t *format*
One of DER or PEM

DESCRIPTION

This function will convert the given DER or PEM encoded CRL to the native **gnutls_x509_crl_t** format. The output will be stored in '*crl*'.

If the CRL is PEM encoded it should have a header of "X509 CRL".

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>