

NAME

gnutls_x509_crl_set_authority_key_id - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_set_authority_key_id(gnutls_x509_crl_t crl, const void * id, size_t id_size);
```

ARGUMENTS

gnutls_x509_crl_t crl
a CRL of type **gnutls_x509_crl_t**

const void * id
The key ID

size_t id_size Holds the size of the serial field.

DESCRIPTION

This function will set the CRL's authority key ID extension. Only the keyIdentifier field can be set with this function. This may be used by an authority that holds multiple private keys, to distinguish the used key.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.8.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>