

NAME

gnutls_x509_crl_set_crt_serial - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_set_crt_serial(gnutls_x509_crl_t crl, const void * serial, size_t serial_size, time_t revocation_time);
```

ARGUMENTS

gnutls_x509_crl_t *crl*
should contain a gnutls_x509_crl_t type

const void * *serial*
The revoked certificate's serial number

size_t *serial_size*
Holds the size of the serial field.

time_t *revocation_time*
The time this certificate was revoked

DESCRIPTION

This function will set a revoked certificate's serial number to the CRL.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>