

NAME

gnutls_x509_crl_set_number - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_set_number(gnutls_x509_crl_t crl, const void * nr, size_t nr_size);
```

ARGUMENTS

gnutls_x509_crl_t *crl*
a CRL of type **gnutls_x509_crl_t**

const void * *nr*
The CRL number

size_t *nr_size* Holds the size of the *nr* field.

DESCRIPTION

This function will set the CRL's number extension. This is to be used as a unique and monotonic number assigned to the CRL by the authority.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.8.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>