

NAME

gnutls_x509_crl_sign2 - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crl_sign2(gnutls_x509_crl_t crl, gnutls_x509_cert_t issuer, gnutls_x509_privkey_t  
issuer_key, gnutls_digest_algorithm_t dig, unsigned int flags);
```

ARGUMENTS

gnutls_x509_crl_t *crl*
should contain a gnutls_x509_crl_t type

gnutls_x509_cert_t *issuer*
is the certificate of the certificate issuer

gnutls_x509_privkey_t *issuer_key*
holds the issuer's private key

gnutls_digest_algorithm_t *dig*
The message digest to use. GNUTLS_DIG_SHA256 is the safe choice unless you know what you're doing.

unsigned int *flags*
must be 0

DESCRIPTION

This function will sign the CRL with the issuer's private key, and will copy the issuer's information into the CRL.

This must be the last step in a certificate CRL since all the previously set parameters are now signed.

A known limitation of this function is, that a newly-signed CRL will not be fully functional (e.g., for signature verification), until it is exported and re-imported.

After GnuTLS 3.6.1 the value of *dig* may be **GNUTLS_DIG_UNKNOWN**, and in that case, a suitable but reasonable for the key algorithm will be selected.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>