

NAME

gnutls_x509_crq_export2 - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_export2(gnutls_x509_crq_t crq, gnutls_x509 crt_fmt_t format, gnutls_datum_t *
out);
```

ARGUMENTS

gnutls_x509_crq_t crq

should contain a **gnutls_x509_crq_t** type

gnutls_x509 crt_fmt_t format

the format of output params. One of PEM or DER.

gnutls_datum_t * out

will contain a certificate request PEM or DER encoded

DESCRIPTION

This function will export the certificate request to a PEM or DER encoded PKCS10 structure.

The output buffer is allocated using **gnutls_malloc()**.

If the structure is PEM encoded, it will have a header of "BEGIN NEW CERTIFICATE REQUEST".

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

Since 3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>