

gnutls\_x509\_crq\_get\_signature\_algorithm(3) gnutls gnutls\_x509\_crq\_get\_signature\_algorithm(3)

## NAME

gnutls\_x509\_crq\_get\_signature\_algorithm - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_get_signature_algorithm(gnutls_x509_crq_t crq);
```

## ARGUMENTS

gnutls\_x509\_crq\_t crq  
should contain a **gnutls\_x509\_cr\_t** type

## DESCRIPTION

This function will return a value of the **gnutls\_sign\_algorithm\_t** enumeration that is the signature algorithm that has been used to sign this certificate request.

Since 3.6.0 this function never returns a negative error code. Error cases and unknown/unsupported signature algorithms are mapped to **GNUTLS\_SIGN\_UNKNOWN**.

## RETURNS

a **gnutls\_sign\_algorithm\_t** value

## SINCE

3.4.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>