

## NAME

gnutls\_x509\_crq\_get\_spki - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_get_spki(gnutls_x509_crq_t crq, gnutls_x509_spki_t spki, unsigned int flags);
```

## ARGUMENTS

gnutls\_x509\_crq\_t crq

should contain a **gnutls\_x509\_crq\_t** type

gnutls\_x509\_spki\_t spki

a SubjectPublicKeyInfo structure of type **gnutls\_x509\_spki\_t**

unsigned int flags

must be zero

## DESCRIPTION

This function will return the public key information of a PKCS10 certificate request. The provided *spki* must be initialized.

## RETURNS

Zero on success, or a negative error code on error.

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>