

gnutls\_x509\_crq\_set\_challenge\_password(3) gnutls gnutls\_x509\_crq\_set\_challenge\_password(3)

## NAME

gnutls\_x509\_crq\_set\_challenge\_password - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_set_challenge_password(gnutls_x509_crq_t crq, const char * pass);
```

## ARGUMENTS

gnutls\_x509\_crq\_t crq  
should contain a **gnutls\_x509\_crq\_t** type

const char \* pass  
holds a (0)-terminated password

## DESCRIPTION

This function will set a challenge password to be used when revoking the request.

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.  
Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.  
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>