

NAME

gnutls_x509_crq_set_key_rsa_raw - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_set_key_rsa_raw(gnutls_x509_crq_t crq, const gnutls_datum_t * m, const gnutls_datum_t * e);
```

ARGUMENTS

gnutls_x509_crq_t crq
should contain a **gnutls_x509_crq_t** type

const gnutls_datum_t * m
holds the modulus

const gnutls_datum_t * e
holds the public exponent

DESCRIPTION

This function will set the public parameters from the given private key to the request. Only RSA keys are currently supported.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.6.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>