

gnutls_x509_crq_set_subject_alt_name(3) gnutls gnutls_x509_crq_set_subject_alt_name(3)

NAME

gnutls_x509_crq_set_subject_alt_name - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_set_subject_alt_name(gnutls_x509_crq_t crq, gnutls_x509_subject_alt_name_t nt,  
const void * data, unsigned int data_size, unsigned int flags);
```

ARGUMENTS

gnutls_x509_crq_t crq

a certificate request of type **gnutls_x509_crq_t**

gnutls_x509_subject_alt_name_t nt

is one of the **gnutls_x509_subject_alt_name_t** enumerations

const void * data

The data to be set

unsigned int data_size

The size of data to be set

unsigned int flags

GNUTLS_FSAN_SET to clear previous data or **GNUTLS_FSAN_APPEND** to append.

DESCRIPTION

This function will set the subject alternative name certificate extension. It can set the following types:

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.8.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>