

NAME

gnutls_x509_crq_set_tlsfeatures - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_set_tlsfeatures(gnutls_x509_crq_t crq, gnutls_x509_tlsfeatures_t features);
```

ARGUMENTS

gnutls_x509_crq_t *crq*

An X.509 certificate request

gnutls_x509_tlsfeatures_t *features*

If the function succeeds, the features will be added to the certificate request.

DESCRIPTION

This function will set the certificate request's X.509 TLS extension from the given structure.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.5.1

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>