

NAME

gnutls_x509_crq_sign2 - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crq_sign2(gnutls_x509_crq_t crq, gnutls_x509_privkey_t key,  
gnutls_digest_algorithm_t dig, unsigned int flags);
```

ARGUMENTS

gnutls_x509_crq_t crq
should contain a **gnutls_x509_crq_t** type

gnutls_x509_privkey_t key
holds a private key

gnutls_digest_algorithm_t dig
The message digest to use, i.e., **GNUTLS_DIG_SHA256**

unsigned int flags
must be 0

DESCRIPTION

This function will sign the certificate request with a private key. This must be the same key as the one used in **gnutls_x509 crt_set_key()** since a certificate request is self signed.

This must be the last step in a certificate request generation since all the previously set parameters are now signed.

A known limitation of this function is, that a newly-signed request will not be fully functional (e.g., for signature verification), until it is exported and re-imported.

After GnuTLS 3.6.1 the value of *dig* may be **GNUTLS_DIG_UNKNOWN**, and in that case, a suitable but reasonable for the key algorithm will be selected.

RETURNS

GNUTLS_E_SUCCESS on success, otherwise a negative error code.

GNUTLS_E_ASN1_VALUE_NOT_FOUND is returned if you didn't set all information in the certificate request (e.g., the version using **gnutls_x509_crq_set_version()**).

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>