

gnutls_x509_crt_cpy_crl_dist_points(3) gnutls gnutls_x509_crt_cpy_crl_dist_points(3)

NAME

gnutls_x509_crt_cpy_crl_dist_points - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_crt_cpy_crl_dist_points(gnutls_x509_crt_t dst, gnutls_x509_crt_t src);
```

ARGUMENTS

gnutls_x509_crt_t dst

a certificate of type **gnutls_x509_crt_t**

gnutls_x509_crt_t src

the certificate where the dist points will be copied from

DESCRIPTION

This function will copy the CRL distribution points certificate extension, from the source to the destination certificate. This may be useful to copy from a CA certificate to issued ones.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>