

**NAME**

gnutls\_x509\_cert\_get\_dn2 - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_get_dn2(gnutls_x509_cert_t cert, gnutls_datum_t * dn);
```

**ARGUMENTS**

gnutls\_x509\_cert\_t cert

should contain a **gnutls\_x509\_cert\_t** type

gnutls\_datum\_t \* dn

a pointer to a structure to hold the name; must be freed using **gnutls\_free()**

**DESCRIPTION**

This function will allocate buffer and copy the name of the Certificate. The name will be in the form "C=xxxx,O=yyyy,CN=zzzz" as described in RFC4514. The output string will be ASCII or UTF-8 encoded, depending on the certificate data.

This function does not output a fully RFC4514 compliant string, if that is required see **gnutls\_x509\_cert\_get\_dn3()**.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

3.1.10

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>