

NAME

gnutls_x509_cert_get_issuer_dn_oid - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_get_issuer_dn_oid(gnutls_x509_cert_t cert, unsigned indx, void * oid, size_t * oid_size);
```

ARGUMENTS

gnutls_x509_cert_t cert

should contain a **gnutls_x509_cert_t** type

unsigned indx This specifies which OID to return. Use (0) to get the first one.

void * oid a pointer to a buffer to hold the OID (may be null)

size_t * oid_size

initially holds the size of *oid*

DESCRIPTION

This function will extract the OIDs of the name of the Certificate issuer specified by the given index.

If *oid* is null then only the size will be filled. The *oid* returned will be null terminated, although *oid_size* will not account for the trailing null.

RETURNS

GNUTLS_E_SHORT_MEMORY_BUFFER if the provided buffer is not long enough, and in that case the *buf_size* will be updated with the required size.

GNUTLS_E_REQUESTED_DATA_NOT_AVAILABLE if there are no data in the current index. On success 0 is returned.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>