

NAME

gnutls_x509_cert_get_raw_issuer_dn - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_get_raw_issuer_dn(gnutls_x509_cert_t cert, gnutls_datum_t * dn);
```

ARGUMENTS

gnutls_x509_cert_t cert

should contain a **gnutls_x509_cert_t** type

gnutls_datum_t * dn

will hold the starting point of the DN

DESCRIPTION

This function will return a pointer to the DER encoded DN structure and the length. This points to allocated data that must be free'd using **gnutls_free()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value or a negative error code on error.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>