

**NAME**

gnutls\_x509\_cert\_get\_raw\_issuer\_dn - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_get_raw_issuer_dn(gnutls_x509_cert_t cert, gnutls_datum_t * dn);
```

**ARGUMENTS**

gnutls\_x509\_cert\_t cert

should contain a **gnutls\_x509\_cert\_t** type

gnutls\_datum\_t \* dn

will hold the starting point of the DN

**DESCRIPTION**

This function will return a pointer to the DER encoded DN structure and the length. This points to allocated data that must be free'd using **gnutls\_free()**.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value or a negative error code on error.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>