

NAME

gnutls_x509_cert_set_ca_status - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_ca_status(gnutls_x509_cert_t crt, unsigned int ca);
```

ARGUMENTS

gnutls_x509_cert_t crt

a certificate of type **gnutls_x509_cert_t**

unsigned int ca

true(1) or false(0). Depending on the Certificate authority status.

DESCRIPTION

This function will set the basicConstraints certificate extension. Use

gnutls_x509_cert_set_basic_constraints() if you want to control the pathLenConstraint field too.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>