

NAME

gnutls_x509_cert_set_crl_dist_points2 - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_crl_dist_points2(gnutls_x509_cert_t crt, gnutls_x509_subject_alt_name_t type,  
const void * data, unsigned int data_size, unsigned int reason_flags);
```

ARGUMENTS

gnutls_x509_cert_t crt

a certificate of type **gnutls_x509_cert_t**

gnutls_x509_subject_alt_name_t type

is one of the gnutls_x509_subject_alt_name_t enumerations

const void * data

The data to be set

unsigned int data_size

The data size

unsigned int reason_flags

revocation reasons

DESCRIPTION

This function will set the CRL distribution points certificate extension.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

2.6.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>