

**NAME**

gnutls\_x509\_cert\_set\_flags - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
void gnutls_x509_cert_set_flags(gnutls_x509_cert_t cert, unsigned int flags);
```

**ARGUMENTS**

gnutls\_x509\_cert\_t cert

A type **gnutls\_x509\_cert\_t**

unsigned int flags

flags from the **gnutls\_x509\_cert\_flags**

**DESCRIPTION**

This function will set flags for the specified certificate. Currently this is useful for the **GNUTLS\_X509\_CERT\_FLAG\_IGNORE\_SANITY** which allows importing certificates even if they have known issues.

**SINCE**

3.6.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>