

NAME

gnutls_x509_cert_set_pin_function - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
void gnutls_x509_cert_set_pin_function(gnutls_x509_cert_t crt, gnutls_pin_callback_t fn, void *  
userdata);
```

ARGUMENTS

gnutls_x509_cert_t *crt*
The certificate structure

gnutls_pin_callback_t *fn*
the callback

void * *userdata*
data associated with the callback

DESCRIPTION

This function will set a callback function to be used when it is required to access a protected object. This function overrides the global function set using **gnutls_pkcs11_set_pin_function()**.

Note that this callback is currently used only during the import of a PKCS **11** certificate with **gnutls_x509_cert_import_url()**.

SINCE

3.1.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>