

NAME

gnutls_x509_cert_set_policy - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_policy(gnutls_x509_cert_t crt, const struct gnutls_x509_policy_st * policy,  
unsigned int critical);
```

ARGUMENTS

gnutls_x509_cert_t crt

should contain a **gnutls_x509_cert_t** type

const struct gnutls_x509_policy_st * policy

A pointer to a policy

unsigned int critical

use non-zero if the extension is marked as critical

DESCRIPTION

This function will set the certificate policy extension (2.5.29.32). Multiple calls to this function append a new policy.

Note the maximum text size for the qualifier **GNUTLS_X509_QUALIFIER_NOTICE** is 200 characters. This function will fail with **GNUTLS_E_INVALID_REQUEST** if this is exceeded.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.1.5

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>