

**NAME**

gnutls\_x509\_cert\_set\_pubkey - API function

**SYNOPSIS**

```
#include <gnutls/abstract.h>
```

```
int gnutls_x509_cert_set_pubkey(gnutls_x509_cert_t crt, gnutls_pubkey_t key);
```

**ARGUMENTS**

gnutls\_x509\_cert\_t crt  
should contain a **gnutls\_x509\_cert\_t** type

gnutls\_pubkey\_t key  
holds a public key

**DESCRIPTION**

This function will set the public parameters from the given public key to the certificate. The *key* can be deallocated after that.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

2.12.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>