

## NAME

gnutls\_x509\_cert\_set\_subject\_unique\_id - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_cert_set_subject_unique_id(gnutls_x509_cert_t cert, const void * id, size_t id_size);
```

## ARGUMENTS

gnutls\_x509\_cert\_t cert

a certificate of type **gnutls\_x509\_cert\_t**

const void \* id

The unique ID

size\_t id\_size Holds the size of the unique ID.

## DESCRIPTION

This function will set the X.509 certificate's subject unique ID field.

## RETURNS

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

## SINCE

3.4.7

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>