

gnutls_x509_ext_export_crl_dist_points(3) gnutls gnutls_x509_ext_export_crl_dist_points(3)

NAME

gnutls_x509_ext_export_crl_dist_points - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_crl_dist_points(gnutls_x509_crl_dist_points_t cdp, gnutls_datum_t * ext);
```

ARGUMENTS

gnutls_x509_crl_dist_points_t *cdp*

A pointer to an initialized CRL distribution points.

gnutls_datum_t * *ext*

The DER-encoded extension data; must be freed using **gnutls_free()**.

DESCRIPTION

This function will convert the provided policies, to a certificate policy DER encoded extension (2.5.29.31).

The *ext* data will be allocated using **gnutls_malloc()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_x509_ext_export_crl_dist_points(3)

gnutls

gnutls_x509_ext_export_crl_dist_points(3)

<https://www.gnutls.org/manual/>