

gnutls_x509_ext_export_name_constraints(3) gnutls gnutls_x509_ext_export_name_constraints(3)

NAME

gnutls_x509_ext_export_name_constraints - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_name_constraints(gnutls_x509_name_constraints_t nc, gnutls_datum_t *  
ext);
```

ARGUMENTS

gnutls_x509_name_constraints_t *nc*
The nameconstraints

gnutls_datum_t * *ext*
The DER-encoded extension data; must be freed using **gnutls_free()**.

DESCRIPTION

This function will convert the provided name constraints type to a DER-encoded PKIX NameConstraints (2.5.29.30) extension. The output data in *ext* will be allocated using **gnutls_malloc()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

gnutls_x509_ext_export_name_constraints(3)

gnutls

gnutls_x509_ext_export_name_constraints(3)

<https://www.gnutls.org/manual/>