

**NAME**

gnutls\_x509\_ext\_export\_policies - API function

**SYNOPSIS**

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_policies(gnutls_x509_policies_t policies, gnutls_datum_t * ext);
```

**ARGUMENTS**

gnutls\_x509\_policies\_t policies

A pointer to an initialized policies.

gnutls\_datum\_t \* ext

The DER-encoded extension data; must be freed using **gnutls\_free()**.

**DESCRIPTION**

This function will convert the provided policies, to a certificate policy DER encoded extension (2.5.29.32).

The *ext* data will be allocated using **gnutls\_malloc()**.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**SINCE**

3.3.0

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>