

NAME

gnutls_x509_ext_export_private_key_usage_period - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_private_key_usage_period(time_t activation, time_t expiration,  
gnutls_datum_t * ext);
```

ARGUMENTS

time_t activation

The activation time

time_t expiration

The expiration time

gnutls_datum_t * ext

The DER-encoded extension data; must be freed using **gnutls_free()**.

DESCRIPTION

This function will convert the periods provided to a private key usage DER encoded extension (2.5.29.16). The *ext* data will be allocated using **gnutls_malloc()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>