

gnutls_x509_ext_export_subject_key_id(3) gnutls gnutls_x509_ext_export_subject_key_id(3)

NAME

gnutls_x509_ext_export_subject_key_id - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_export_subject_key_id(const gnutls_datum_t * id, gnutls_datum_t * ext);
```

ARGUMENTS

const gnutls_datum_t * id
The key identifier

gnutls_datum_t * ext
The DER-encoded extension data; must be freed using **gnutls_free()**.

DESCRIPTION

This function will convert the provided key identifier to a DER-encoded PKIX SubjectKeyIdentifier extension. The output data in *ext* will be allocated using **gnutls_malloc()**.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.
Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>