#### **NAME**

```
gnutls_x509_ext_import_inhibit_anypolicy - API function
```

#### **SYNOPSIS**

#include <gnutls/x509-ext.h>

int gnutls\_x509\_ext\_import\_inhibit\_anypolicy(const gnutls\_datum\_t \* ext, unsigned int \* skipcerts);

# **ARGUMENTS**

```
const gnutls_datum_t * ext
the DER encoded extension data
```

unsigned int \* skipcerts

will hold the number of certificates after which anypolicy is no longer acceptable.

#### **DESCRIPTION**

This function will return certificate's value of SkipCerts, by reading the DER data of the Inhibit anyPolicy X.509 extension (2.5.29.54).

The *skipcerts* value is the number of additional certificates that may appear in the path before the anyPolicy (GNUTLS\_X509\_OID\_POLICY\_ANY) is no longer acceptable.

### **RETURNS**

zero, or a negative error code in case of parsing error. If the certificate does not contain the Inhibit anyPolicy extension **GNUTLS\_E\_REQUESTED\_DATA\_NOT\_AVAILABLE** will be returned.

## **SINCE**

3.6.0

### **REPORTING BUGS**

Report bugs to <bugs@gnutls.org>. Home page: https://www.gnutls.org

### **COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## **SEE ALSO**

gnutls

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/directory does not contain the HTML form visit

https://www.gnutls.org/manual/