

NAME

gnutls_x509_ext_import_key_purposes - API function

SYNOPSIS

```
#include <gnutls/x509-ext.h>
```

```
int gnutls_x509_ext_import_key_purposes(const gnutls_datum_t * ext, gnutls_x509_key_purposes_t p,
unsigned int flags);
```

ARGUMENTS

const gnutls_datum_t * *ext*

The DER-encoded extension data

gnutls_x509_key_purposes_t *p*

The key purposes

unsigned int *flags*

should be zero

DESCRIPTION

This function will extract the key purposes in the provided DER-encoded ExtKeyUsageSyntax PKIX extension, to a **gnutls_x509_key_purposes_t** type. The data must be initialized.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

SINCE

3.3.0

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>