

NAME

gnutls_x509_privkey_export2 - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_privkey_export2(gnutls_x509_privkey_t key, gnutls_x509_cert_fmt_t format,  
gnutls_datum_t * out);
```

ARGUMENTS

gnutls_x509_privkey_t key
Holds the key

gnutls_x509_cert_fmt_t format
the format of output params. One of PEM or DER.

gnutls_datum_t * out
will contain a private key PEM or DER encoded

DESCRIPTION

This function will export the private key to a PKCS1 structure for RSA or RSA-PSS keys, and integer sequence for DSA keys. Other keys types will be exported in PKCS8 form.

The output buffer is allocated using **gnutls_malloc()**.

It is recommended to use **gnutls_x509_privkey_export2_pkcs8()** instead of this function, when a consistent output format is required.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

Since 3.1.3

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>