

NAME

gnutls_x509_privkey_import2 - API function

SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_privkey_import2(gnutls_x509_privkey_t key, const gnutls_datum_t * data,  
gnutls_x509_crt_fmt_t format, const char * password, unsigned int flags);
```

ARGUMENTS

gnutls_x509_privkey_t key

The data to store the parsed key

const gnutls_datum_t * data

The DER or PEM encoded key.

gnutls_x509_crt_fmt_t format

One of DER or PEM

const char * password

A password (optional)

unsigned int flags

an ORed sequence of gnutls_pkcs_encrypt_flags_t

DESCRIPTION

This function will import the given DER or PEM encoded key, to the native **gnutls_x509_privkey_t** format, irrespective of the input format. The input format is auto-detected.

The supported formats are basic unencrypted key, PKCS8, PKCS12, and the openssl format.

If the provided key is encrypted but no password was given, then

GNUTLS_E_DECRYPTION_FAILED is returned. Since GnuTLS 3.4.0 this function will utilize the PIN callbacks if any.

RETURNS

On success, **GNUTLS_E_SUCCESS** (0) is returned, otherwise a negative error value.

REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>