

**NAME**

gnutls\_x509\_privkey\_import\_openssl - API function

**SYNOPSIS**

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_privkey_import_openssl(gnutls_x509_privkey_t key, const gnutls_datum_t * data,  
const char * password);
```

**ARGUMENTS**

gnutls\_x509\_privkey\_t key

The data to store the parsed key

const gnutls\_datum\_t \* data

The DER or PEM encoded key.

const char \* password

the password to decrypt the key (if it is encrypted).

**DESCRIPTION**

This function will convert the given PEM encrypted to the native gnutls\_x509\_privkey\_t format. The output will be stored in *key*.

The *password* should be in ASCII. If the password is not provided or wrong then

**GNUTLS\_E\_DECRYPTION\_FAILED** will be returned.

If the Certificate is PEM encoded it should have a header of "PRIVATE KEY" and the "DEK-Info" header.

**RETURNS**

On success, **GNUTLS\_E\_SUCCESS** (0) is returned, otherwise a negative error value.

**REPORTING BUGS**

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

**COPYRIGHT**

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium

without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>