

## NAME

gnutls\_x509\_spki\_get\_rsa\_pss\_params - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_spki_get_rsa_pss_params(gnutls_x509_spki_t spki, gnutls_digest_algorithm_t * dig,  
unsigned int * salt_size);
```

## ARGUMENTS

gnutls\_x509\_spki\_t *spki*  
the SubjectPublicKeyInfo structure

gnutls\_digest\_algorithm\_t \* *dig*  
if non-NULL, it will hold the digest algorithm

unsigned int \* *salt\_size*  
if non-NULL, it will hold the salt size

## DESCRIPTION

This function will get the public key algorithm parameters of RSA-PSS type.

## RETURNS

zero if the parameters are present or a negative value on error.

## SINCE

3.6.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/`

gnutls\_x509\_spki\_get\_rsa\_pss\_params(3)

gnutls

gnutls\_x509\_spki\_get\_rsa\_pss\_params(3)

directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>