

## NAME

gnutls\_x509\_trust\_list\_remove\_trust\_file - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
int gnutls_x509_trust_list_remove_trust_file(gnutls_x509_trust_list_t list, const char * ca_file,  
gnutls_x509_cert_fmt_t type);
```

## ARGUMENTS

gnutls\_x509\_trust\_list\_t list

The list

const char \* ca\_file

A file containing a list of CAs

gnutls\_x509\_cert\_fmt\_t type

The format of the certificates

## DESCRIPTION

This function will remove the given certificate authorities from the trusted list, and add them into a black list when needed. PKCS 11 URLs are also accepted, instead of files, by this function.

See also **gnutls\_x509\_trust\_list\_remove\_cas()**.

## RETURNS

The number of added elements is returned.

## SINCE

3.1.10

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001- Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gnutls** is maintained as a Texinfo manual. If the `/usr/local/share/doc/gnutls/` directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>