

## NAME

gnutls\_x509\_trust\_list\_set\_ptr - API function

## SYNOPSIS

```
#include <gnutls/x509.h>
```

```
void gnutls_x509_trust_list_set_ptr(gnutls_x509_trust_list_t tlist, void * ptr);
```

## ARGUMENTS

gnutls\_x509\_trust\_list\_t tlist  
is a **gnutls\_x509\_trust\_list\_t** type.

void \* ptr is the user pointer

## DESCRIPTION

This function will set (associate) the user given pointer *ptr* to the tlist structure. This pointer can be accessed with **gnutls\_x509\_trust\_list\_get\_ptr()**. Useful in the callback function **gnutls\_x509\_trust\_list\_set\_getissuer\_function**.

## SINCE

3.7.0

## REPORTING BUGS

Report bugs to <bugs@gnutls.org>.

Home page: <https://www.gnutls.org>

## COPYRIGHT

Copyright (C) 2001-2023 Free Software Foundation, Inc., and others.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

## SEE ALSO

The full documentation for **gnutls** is maintained as a Texinfo manual. If the /usr/local/share/doc/gnutls/ directory does not contain the HTML form visit

<https://www.gnutls.org/manual/>