

NAME

gsasl_check_version - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
const char * gsasl_check_version(const char * req_version);
```

ARGUMENTS

const char * req_version
version string to compare with, or NULL.

DESCRIPTION

Check GNU SASL Library version.

See **GSASL_VERSION** for a suitable *req_version* string.

This function is one of few in the library that can be used without a successful call to **gsasl_init()**.

Return value: Check that the version of the library is at minimum the one given as a string in *req_version* and return the actual version string of the library; return NULL if the condition is not met. If NULL is passed to this function no check is done and only the version string is returned.

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.
General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>
GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.
Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

info gsasl

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>