

NAME

gsasl_encode - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
int gsasl_encode(Gsasl_session * sctx, const char * input, size_t input_len, char ** output, size_t * output_len);
```

ARGUMENTS

Gsasl_session * sctx

libgsasl session handle.

const char * input

input byte array.

size_t input_len

size of input byte array.

char ** output

newly allocated output byte array.

size_t * output_len

pointer to output variable with size of output byte array.

DESCRIPTION

Encode data according to negotiated SASL mechanism. This might mean that data is integrity or privacy protected.

The *output* buffer is allocated by this function, and it is the responsibility of caller to deallocate it by calling `gsasl_free(output)`.

Return value: Returns **GSASL_OK** if encoding was successful, otherwise an error code.

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

info gsasl

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>